



TECH DATA SHEET

1. PRODUCT NAME

Touch 'n Seal® Heavy Duty Construction Adhesive

Item # 4001160320
24 ounce

2. MANUFACTURER

Convenience Products
866 Horan Dr.
Fenton, MO 63026 USA
Phone: (636) 349-5855
Toll Free: (800) 325-6180
FAX: (636) 349-5335
E-mail: support@touch-n-seal.com
Website: www.touch-n-seal.com

3. PRODUCT DESCRIPTION

Touch 'n Seal Heavy Duty Construction Adhesive is a high performance one-component moisture-cured polyurethane adhesive for permanently bonding to wood, drywall, most plastics, metal, fiberglass, carpet, and other common building materials. The adhesive dispenses as a foam froth, but quickly collapses to a viscous liquid gel to increase bond strength. As the adhesive cures, it expands slightly to fill any gaps between the substrates.

Basic Use

Touch 'n Seal Heavy Duty Construction Adhesive can be used as an adhesive seal between drywall (gypsum) and wood studs to increase the structural strength of walls in the modular and manufactured home industries. In new construction, it is also used as an air seal for wall cavities and headers, and to seal sill plates against foundation walls.

Features/Benefits

- Exceeds adhesion requirements of ASTM C557 and D6464 for adhering drywall to wood studs
- Performance tested and certified by PFS, an independent material testing and certification lab for wood related construction products
- Faster and easier to apply than caulk adhesives and sealants
- One 24 oz. can of Touch 'n Seal Heavy Duty Construction Adhesive has the same or greater coverage as ten 28 oz. caulk tubes

4. TECHNICAL DATA

Applicable Methods & Standards

- ASTM C557, Standard Specification for Adhesives for Fastening Gypsum Wallboard to Wood Framing
- ASTM D6464, Standard Specification for Adhesives for Fastening Gypsum Wallboard to Wood Framing
- ASTM D905, Test Method for Strength Properties of Adhesive Bonds in Shear by Compression Loading
- ASTM D572, Test Method for Rubber-Deterioration by Heat and Oxygen

5. SAFE USE AND HANDLING

- Refer to product Safety Data Sheet (SDS) prior to handling or using Touch 'n Seal products.

- Always wear protective clothing, gloves and eyewear to protect from skin and eye exposure
- Keep away from flame, sparks, excessive heat or other sources of ignition
- Use in well-ventilated area
- Do not store in hot vehicle, direct sunlight or temperatures above 120°F (49°C)
- Keep out of reach of children.

CAUTION: Contains MDI monomer, polyurethane resin, and propane/isobutene. Cured foam exposed to temperatures greater than 240°F (116°C) may release hazardous decomposition products.

Storage & Disposal

- Keep containers tightly closed in a cool, well-ventilated area. Ideal storage temperature is 60°-90°F (16°-32°C). Storage above 90°F (32°C) will reduce shelf life. Do not store at temperatures above 120°F (49°C). Avoid Freezing. Do not expose containers to conditions that may damage, puncture, or burst the containers. Dispose of leftover material/containers in accordance with Federal, state and local regulations. See Safety Data Sheet for more information.

Shelf Life

12 months in unopened container when stored between 60° - 90°F (16° - 32°C), in a dry, well-ventilated area.

6. INSTALLATION / APPLICATION

Preparation

1. Foam bonds quickly to skin – wear gloves, eye protection and work clothes during application. Use drop cloths where necessary. Not for overhead use.
2. Surface should be free of oil, grease, and excess moisture. For best results apply in temperatures between 60°F-100°F (16°F-37°F).
3. For easy attachment, apply petroleum jelly to applicator basket before attaching can. While pointing applicator in a safe direction, depress trigger and attach applicator to can. (See directions inside applicator carton.) Do not over-tighten.
4. After attaching applicator to can, shake vigorously for 30 seconds.
5. Dispense foam with can in upside down position. Test and adjust bead size on scrap material.

Drywall: Apply a continuous ½ inch bead to face of stud or framing member. To avoid dripping, set drywall within five minutes and install nails or screws to secure.

Other Applications: Clamping or blocking may be necessary.

Can Replacement:

1. To replace empty can, point applicator in a safe direction, depress trigger and quickly remove empty can.
2. Spray basket with Touch 'n Seal Poly-Clean Foam Cleaner and immediately attach new can.



Convenience Products
866 Horan Dr., Fenton, MO 63026 USA
(800) 325-6180, (636) 349-5855 tel.



54038-010815-TNS



TECH DATA SHEET

Storage:

1. Turn applicator's flow control knob to closed position and store can in an upright position (with gun still attached.)
2. To restart, shake well for 30 seconds, turn flow control knob to open position and dispense foam.
3. Maximum storage: 15 days.

7. AVAILABILITY

Contact Convenience Products Customer Service at 800-325-6180 (Press "1") for distributor information.

8. WARRANTY

Convenience Products warrants this product to be free from defects. The Company shall not be liable for any consequential or other damage or remedy; its sole obligation and your exclusive remedy are limited to product replacement. Warranty is null and

void if unit is operated without attaching a new spray foam applicator gun/hose set. Some states do not allow limitations on the exclusive or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. There are no warranties which extend beyond the description on the face hereof.

9. MAINTENANCE

Refer to Applicator Operation Instructions."

10. TECHNICAL SERVICE

Technical assistance, including detailed information, product literature, test results, assistance with preparing project specifications and application training is available by contacting Convenience Products

TYPICAL PROPERTIES OF Touch 'n Seal® Heavy Duty Construction Adhesive

Property	Typical Values	
Appearance	Grey foam collapses to black liquid gel	
Shelf Life	18 months	
Open Time	20 minutes	
Fully Cured	4 hours	
Yield at ½" bead size	480 Linear feet	
Application Temperature Range	23° -100°F	
VOC Content	156 g/l	
ASTM C557 / D6464	C557	D6464
Shear Strength, 24 hours	91 psi	95 psi
Shear Strength, 14 days	104 psi	89 psi
Shear Strength, Cyclic Exposure	108 psi	104 psi
Tensile Strength, 24 hours	36 psi	45 psi
Tensile Strength, 14 days	39 psi	34 psi
Shear Strength, Freeze/Thaw	105 psi	111 psi
Shear Strength under Static Load, 20 lb., 40 lb.	Pass, Pass	Pass, Pass
Wet Out, Plywood, Drywall	Pass	
Aging	Pass	Pass
Laminating Suitability, Compatibility, Staining	Pass, Pass, Pass	
Gap Filling / Bridging	Pass, 42 inches	Pass, 42 inches

The information contained herein was accurate at the time of publishing. Please refer to the Touch 'N Seal website for the latest information.



Convenience Products
866 Horan Dr., Fenton, MO 63026 USA
(800) 325-6180, (636) 349-5855 tel.



54038-010815-TNS