

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

## 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Touch 'n Seal Liner Bond Adhesive
- **Article number:** EHS 9466
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Convenience Products, division of Clayton Corp.  
866 Horan Drive  
Fenton, MO 63026-2416  
Phone: 636-349-5855
- **1.4 Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585



## 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT SE 3 H335 May cause respiratory irritation.

H229 Pressurised container: May burst if heated.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20: Harmful by inhalation.



Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.



Xi; Irritant

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 1)

R36/37/38: Irritating to eyes, respiratory system and skin.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomeres and homologues  
4,4'-methylenediphenyl diisocyanate  
trans-dichloroethylene

· **Hazard statements**

H229 Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P280 Wear protective gloves / eye protection.

P260 Do not breathe mist/vapours/spray.

P314 Get medical advice/attention if you feel unwell.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· **Additional information:**

Contains isocyanates. May produce an allergic reaction.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 2)

- **Hazard description:**
- **WHMIS-symbols:**  
A - Compressed gas  
D2A - Very toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



\* - Indicates a long term health hazard from repeated or prolonged exposures.

**HMIS Long Term Health Hazard Substances**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
101-68-8	4,4'-methylenediphenyl diisocyanate

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues   	20-40%
CAS: 811-97-2 EINECS: 212-377-0	Norflurane 	20-40%

(Contd. on page 4)







# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

		(Contd. of page 3)
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9	4,4'-methylenediphenyl diisocyanate  Carc. Cat. 3 <hr/>  	10-20%
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate R52/53 Aquatic Chronic 3, H412	10-20%
CAS: 156-60-5 EINECS: 205-860-2 Index number: 602-026-00-3	trans-dichloroethylene  R52/53 <hr/>   Aquatic Chronic 3, H412	1-5%
CAS: 8001-22-7 EINECS: 232-274-4	Soybean Oil substance with a Community workplace exposure limit	1-5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

## 4 First aid measures

### · 4.1 Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

#### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not pull solidified product off the skin.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Immediately remove contact lenses if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

### · 4.2 Most important symptoms and effects, both acute and delayed

Asthma attacks

Headache

Breathing difficulty

Allergic reactions

Coughing

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 4)

Nausea

Gastric or intestinal disorders when ingested.

Irritant to skin and mucous membranes.

Irritant to eyes.

Dizziness

Disorientation

- **Hazards**

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

Danger of pulmonary oedema.

Danger of pneumonia.

Danger of convulsion.

- **4.3 Indication of any immediate medical attention and special treatment needed**

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

In cases of irritation to the lungs, initial treatment with corticoid steroid inhalants.

Monitor circulation.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Contains isocyanates. May produce an allergic reaction.

## 5 Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Water in flooding quantities.

- **For safety reasons unsuitable extinguishing agents:** None.

- **5.2 Special hazards arising from the substance or mixture**

Danger of receptacles bursting because of high vapour pressure when heated.

During heating or in case of fire poisonous gases are produced.

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information** Cool endangered receptacles with water spray.

## 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Protect from heat.

Isolate area and prevent access.

Keep people at a distance and stay on the windward side.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 5)

· **6.3 Methods and material for containment and cleaning up:**

- Allow to solidify. Pick up mechanically.
- Send for recovery or disposal in suitable receptacles.
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.

· **6.4 Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

## 7 Handling and storage

· **7.1 Precautions for safe handling**

- Keep away from heat and direct sunlight.
- Use only in well ventilated areas.

· **Information about fire - and explosion protection:**

- Keep respiratory protective device available.
- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- Do not spray onto a naked flame or any incandescent material.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

- Store in a cool location.
- Observe official regulations on storing packagings with pressurized containers.
- Provide ventilation for receptacles.
- Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

- Store away from foodstuffs.
- Store away from oxidizing agents.

· **Further information about storage conditions:**

- Protect from heat and direct sunlight.
- Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· **7.3 Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**811-97-2 Norflurane**

WEEL (USA)	Long-term value: 1000 ppm
------------	---------------------------

(Contd. on page 7)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 6)

**101-68-8 4,4'-methylenediphenyl diisocyanate**

PEL (USA)	Ceiling limit: 0,2 mg/m <sup>3</sup> , 0,02 ppm
REL (USA)	Long-term value: 0,05 mg/m <sup>3</sup> , 0,005 ppm Ceiling limit: 0,2* mg/m <sup>3</sup> , 0,02* ppm *10-min
TLV (USA)	Long-term value: 0,051 mg/m <sup>3</sup> , 0,005 ppm
EL (Canada)	Short-term value: C 0,01 ppm Long-term value: 0,005 ppm Skin; S
EV (Canada)	Long-term value: 0,005 ppm

**156-60-5 trans-dichloroethylene**

PEL (USA)	Long-term value: 790 mg/m <sup>3</sup> , 200 ppm
REL (USA)	Long-term value: 790 mg/m <sup>3</sup> , 200 ppm
TLV (USA)	Long-term value: 793 mg/m <sup>3</sup> , 200 ppm
EL (Canada)	Long-term value: 200 ppm
EV (Canada)	Short-term value: 990 mg/m <sup>3</sup> , 250 ppm Long-term value: 790 mg/m <sup>3</sup> , 200 ppm

**8001-22-7 Soybean Oil**

PEL (USA)	Short-term value: 15* 5** mg/m <sup>3</sup> *Total dust **Respirable fraction
OEL (Canada)	Short-term value: 10* 3** mg/m <sup>3</sup> *Mist **Respirable Mist

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**
**Personal protective equipment:**
**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Clean skin thoroughly immediately after handling the product.

**Respiratory protection:**


Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

(Contd. on page 8)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 7)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

## 9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	Amber coloured
<b>Odour:</b>	Light

<b>Odour threshold:</b>	Petroleum-like
<b>pH-value:</b>	Not determined.

<b>Change in condition</b>	Not determined.
<b>Melting point/Melting range:</b>	-15 °F / -26 °C
<b>Boiling point/Boiling range:</b>	Not determined.

<b>Flash point:</b>	Not applicable, as aerosol.
---------------------	-----------------------------

<b>Flammability (solid, gaseous):</b>	Not applicable.
---------------------------------------	-----------------

(Contd. on page 9)



## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 8)

- **Auto/Self-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapour pressure:** Not determined.
- **Density at 20 °C:** 1,2 g/cm<sup>3</sup>
- **Relative density:** Not determined.
- **Vapour density:** Not determined.
- **Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - VOC (US EPA Method 24)** 49 g/l
- **9.2 Other information** No further relevant information available.

### 10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.  
Contact with acids releases toxic gases.  
Danger of receptacles bursting because of high vapour pressure when heated.
- **10.4 Conditions to avoid** Store away from oxidizing agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (prussic acid)

(Contd. on page 10)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

Phosphorus oxides (e.g. P<sub>2</sub>O<sub>5</sub>)

(Contd. of page 9)

## 11 Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity:

#### LD/LC50 values relevant for classification:

**101-68-8 4,4'-methylenediphenyl diisocyanate**

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

#### Primary irritant effect:

**on the skin:** Irritant to skin and mucous membranes.

**on the eye:** Irritating effect.

#### Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

#### Subacute to chronic toxicity:

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

#### Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Danger through skin adsorption.

Toxic and/or corrosive effects may be delayed up to 24 hours.

In addition to local irritant manifestations, there is a narcotic effect when inhaling high concentrations, with high danger of central respiratory arrest.

**Acute effects (acute toxicity, irritation and corrosivity):** Vapours have narcotic effect.

#### Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

## 12 Ecological information

### 12.1 Toxicity

**Aquatic toxicity:** No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

#### Additional ecological information:

#### General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 11)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 10)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN3500
- **14.2 UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).

- **DOT** Chemical under pressure, n.o.s. (Fluorinated Hydrocarbon, Nitrogen)
- **ADR** 3500 CHEMICAL UNDER PRESSURE, N.O.S. (Fluorinated Hydrocarbon, Nitrogen)
- **IMDG, IATA** CHEMICAL UNDER PRESSURE, N.O.S. (Fluorinated Hydrocarbon, Nitrogen)

- **14.3 Transport hazard class(es)**

- **DOT**



- **Class** 2.2
- **Label** 2.2

- **ADR**



- **Class** 2 5A Gases.

(Contd. on page 12)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

Trade name: Touch 'n Seal Liner Bond Adhesive

(Contd. of page 11)

· Label 2.2

· IMDG, IATA



· Class 2.2  
 · Label 2.2  
 · 14.4 Packing group  
 · DOT, ADR, IMDG, IATA Not Regulated  
 · 14.5 Environmental hazards:  
 · Marine pollutant: No  
 · 14.6 Special precautions for user Warning: Gases.  
 · Danger code (Kemler): -  
 · EMS Number: F-D,S-U  
 · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L  
 · Transport category 3  
 · Tunnel restriction code E  
 · UN "Model Regulation": UN3500, CHEMICAL UNDER PRESSURE, N.O.S. (Fluorinated Hydrocarbon, Nitrogen), 2.2

## 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 13)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 12)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	CBD
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
156-60-5	trans-dichloroethylene	II

· **IARC (International Agency for Research on Cancer)**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3
101-68-8	4,4'-methylenediphenyl diisocyanate	3

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

101-68-8 | 4,4'-methylenediphenyl diisocyanate

· **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients is listed.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 14)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 18.06.2014

Revision: 17.06.2014

**Trade name: Touch 'n Seal Liner Bond Adhesive**

(Contd. of page 13)

H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.  
 R11 Highly flammable.  
 R20 Harmful by inhalation.  
 R36/37/38 Irritating to eyes, respiratory system and skin.  
 R42/43 May cause sensitisation by inhalation and skin contact.  
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 WHMIS: Workplace Hazardous Materials Information System (Canada)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 : Flammable aerosols, Hazard Category 3  
 Press. Gas: Gases under pressure: Compressed gas  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1  
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

**Sources**

SDS Prepared by:  
 ChemTel Inc.  
 1305 North Florida Avenue  
 Tampa, Florida USA 33602-2902  
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573  
 Website: [www.chemtelinc.com](http://www.chemtelinc.com)

4004517114