

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

1 Identification

· Product identifier

· Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

Product code: EHS 2322 A

· Recommended use and restriction on use

· Recommended use: Polyurethane-sealant

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Convenience Products

866 Horan Drive Pacific, MO 63026 Phone: 636-349-5855 Toll-Free: 1-800-325-6180

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Press. Gas H280 Contains gas under pressure; may explode if heated.

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:







GHS04 GHS07 GHS08

· Signal word: Danger

Hazard statements:

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Cont'd. on page 2)

Page: 1/12



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 1)

Page: 2/12

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements:

P233 Keep container tightly closed.
P260 Do not breathe mist/vapors/spray.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection.
P284 In case of inadequate ventilation wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

Compone	nts:	
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
101-68-8	4,4'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
811-97-2	Norflurane Press. Gas, H280 Simple Asphyxiant	10-25%
	halogenated hydrocarbon Flam. Liq. 2, H225 Acute Tox. 4, H332	<10%

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

(Cont'd. on page 3)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 2)

Page: 3/12

For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

Description of first aid measures

· After inhalation:

Supply fresh air and to be sure to call for a doctor.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Do not pull solidified product away from the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Protect unharmed eye.

Do not remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Seek immediate medical advice.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Asthma attacks

Headache

Coughing

Breathing difficulty

Dizziness

Cyanosis

Allergic reactions

Irritant to skin and mucous membranes.

Causes eye irritation.

· Danger:

Danger of impaired breathing.

Danger of pulmonary edema.

Danger of convulsion.

May cause damage to organs through prolonged or repeated exposure.

Condition may deteriorate with alcohol consumption.

Indication of any immediate medical attention and special treatment needed:

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

Contains isocyanates. May produce an allergic reaction.

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

(Cont'd. on page 4)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 3)

Page: 4/12

Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- For safety reasons unsuitable extinguishing agents: None.
- Special hazards arising from the substance or mixture

Danger of receptacles bursting because of high vapor pressure if heated.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information: Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Remove persons from danger area.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Protect from heat.

· Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Clean the affected area carefully; suitable cleaners are:

Organic solvent

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Avoid contact with the eyes and skin.

Keep out of reach of children.

(Cont'd. on page 5)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 4)

Page: 5/12

· Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Store away from oxidizing agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

Control parameters					
· Components with limit values that require monitoring at the workplace:					
101-68-8 4,4'-m	nethylenediphenyl diisocyanate				
PEL (USA)	Ceiling limit value: 0.2 mg/m³, 0.02 ppm				
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min				
TLV (USA)	Long-term value: 0.051 mg/m³, 0.005 ppm				
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S				
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm				
LMPE (Mexico)	Long-term value: 0.005 ppm				
811-97-2 Norflu	urane				
WEEL (USA)	Long-term value: 1000 ppm				
halogenated h	ydrocarbon				
PEL (USA)	Long-term value: 790 mg/m³, 200 ppm				
REL (USA)	Long-term value: 790 mg/m³, 200 ppm				
TLV (USA)	Long-term value: 790 mg/m³, 200 ppm				
EL (Canada)	Long-term value: 200 ppm				
EV (Canada)	Short-term value: 990 mg/m³, 250 ppm Long-term value: 790 mg/m³, 200 ppm				
	(Cont'd. on pag	e 6)			

Contid. on page 6)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 5)

Page: 6/12

LMPE (Mexico) Long-term value: 200 ppm

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

- Engineering controls: No relevant information available.
- **Breathing equipment:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

Suitable respiratory protective device recommended.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties

Information on basic physical and chemical properties

· Appearance:

Form: Aerosolized liquid with compressed gas in cylinders

Color: Cream colored
Odor: Characteristic
Odor threshold: Not determined.

· pH-value: Not determined.

Melting point/Melting range:
 Boiling point/Boiling range:
 Not applicable, as aerosol.
 Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

(Cont'd. on page 7)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

		(Cont'd. of page 6)
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	400 °C (752 °F)	
· Decomposition temperature:	Not determined.	
· Danger of explosion:	Not determined.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
· Oxidizing properties:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	5716 hPa (4287 mm Hg)	
· Density:		
Relative density:	1.03	
Vapor density:	Not determined.	
Evaporation rate:	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC (California):	32.8 g/L (EPA Method 24)	
Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

Danger of receptacles bursting because of high vapor pressure if heated.

· Possibility of hazardous reactions

Reacts with alcohols, amines, aqueous acids and alkalis.

Contact with acids releases toxic gases.

Reacts with oxidizing agents.

Exothermic polymerization.

- · Conditions to avoid Excessive heat.
- · Incompatible materials Contact with acids liberates toxic gas.
- Hazardous decomposition products

Carbon monoxide and carbon dioxide

Ammonia

Isocyanate

(Cont'd. on page 8)

Page: 7/12



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 7)

Page: 8/12

Nitrogen oxides

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- Primary irritant effect:
- On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Sensitization: May cause sensitisation by inhalation and skin contact.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Inhalation.

Eye contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Harmful if inhaled.

Irritating to eyes, respiratory system and skin.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause respiratory irritation.
- · STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity The product contains materials that are harmful to the environment.
- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- · Bioaccumulative potential: Does not accumulate in organisms
- Mobility in soil: No relevant information available.

(Cont'd. on page 9)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 8)

Page: 9/12

Additional ecological information

· General notes:

Due to the consistence and the low watersolubility of the product a bioavailability is not probable.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Contact waste processors for recycling information.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3500
· UN proper shipping name	
DOT, IATA	Chemical under pressure, n.o.s. (Fluorinated hydrocarbon, Nitrogen)
· ADR, IMDG	CHEMICAL UNDER PRESSURE, N.O.S. (FLUORINATED HYDROCARBON, NITROGEN)
· Transport hazard class(es)	
· DOT	
· Class	2.2
	(Cont'd. on page 10



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 9) · Label 2.2 · ADR · Class 2 8A Gases · Label 2.2 · IMDG, IATA · Class 2 Gases · Label 2.2 · Packing group This UN-number is not assigned a packing group. • Environmental hazards · Marine pollutant: No Special precautions for user Warning: Gases Danger code (Kemler): 20 · EMS Number: F-C,S-V Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

(Cont'd. on page 11)

Page: 10/12



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 10)

Page: 11/12

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories

· EPA (Environmental Protection Agency):				
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	CBD		
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD		
	halogenated hydrocarbon	II		

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision April 11, 2017 / -

· Abbreviations and acronyms:

LDLo: Lowest Lethal Dose Observed

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Press. Gas: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

(Cont'd. on page 12)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 11, 2017 Revision: April 11, 2017

Trade name: Touch 'n Seal Mine Foam Kit 180, 200, RF-17 Part A

(Cont'd. of page 11)

Page: 12/12

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by: ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com