Printing date 02.02.2017 Revision: 02.02.2017

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)
- · Article number: EHS 9464
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Sealant
- · 1.3 Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:

Convenience Products, division of Clayton Corp.

866 Horan Drive

Fenton, MO 63026-2416 Phone: 636-349-5855



ChemTel Inc.

(800)255-3924, +1 (813)248-0585



2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

May displace oxygen and cause rapid suffocation. (USA GHS Only)



gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 1)

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20-40: Harmful by inhalation. Limited evidence of a carcinogenic effect.

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

💢 Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H229, H412.

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS04 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues

tris[2-chloro-1-(chloromethyl)ethyl] phosphate

4,4'-methylenediphenyl diisocyanate

trans-dichloroethylene

· Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

May displace oxygen and cause rapid suffocation. (USA GHS Only)

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 3)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 2)

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P285 In case of inadequate ventilation wear respiratory protection.

P281 Use personal protective equipment as required.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.

P314 Get medical advice/attention if you feel unwell.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

3,3 % by mass of the contents are flammable

- Hazard description:
- · WHMIS-symbols:

A - Compressed gas

D2A - Very toxic material causing other toxic effects



· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*2 Health = *2

1 Fire = 1

* - Indicates a long term health hazard from repeated or prolonged exposures.

HMIS Long Term Health Hazard Substances

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 4)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 3)

3 Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues X N R20; X Xn R42/43; Xi R36/37/38 Carc. Cat. 3	
	Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	-
CAS: 811-97-2	Norflurane	
EINECS: 212-377-0	Press. Gas, H280	
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9	4,4'-methylenediphenyl diisocyanate Xn R20; Xn R42/43; Xi R36/37/38 9 Carc. Cat. 3	
	Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate R52/53	10-20%
	Aquatic Chronic 3, H412	
CAS: 13674-87-8 EINECS: 237-159-2	tris[2-chloro-1-(chloromethyl)ethyl] phosphate Xn R40; N R51/53	5-10%
Index number: 015-199-00-X	© Carc. 2, H351 Aquatic Chronic 2, H411	
CAS: 156-60-5	trans-dichloroethylene	1-5%
EINECS: 205-860-2 Index number: 602-026-00-3	Xn R20; b F R11 R52/53	
1110CX 110111DG1. 002-020-00-3	♦ Flam. Liq. 2, H225	
	1 Acute Tox. 4, H332	
	Aquatic Chronic 3, H412	

- Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

(Contd. on page 5)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 4)

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not pull solidified product off the skin.

If skin irritation continues, consult a doctor.

· After eye contact:

Immediately remove contact lenses if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Asthma attacks

Headache

Breathing difficulty

Allergic reactions

Coughing

Nausea

Gastric or intestinal disorders when ingested.

Irritant to skin and mucous membranes.

Irritant to eyes.

Dizziness

Disorientation

· Hazards

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

Danger of pneumonia.

Danger of pulmonary oedema.

Danger of convulsion.

\cdot 4.3 Indication of any immediate medical attention and special treatment needed

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

Monitor circulation.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Contains isocyanates. May produce an allergic reaction.

5 Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Water in flooding quantities.

- · For safety reasons unsuitable extinguishing agents: None.
- · 5.2 Special hazards arising from the substance or mixture

Danger of receptacles bursting because of high vapour pressure when heated.

During heating or in case of fire poisonous gases are produced.

(Contd. on page 6)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 5)

· 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Protect from heat.

Isolate area and prevent access.

Keep people at a distance and stay on the windward side.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

(Contd. on page 7)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 6)

· Further information about storage conditions:

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· 6.1 Control parameters						
· Ingredients with limit values that require monitoring at the workplace:						
811-97-2 Norflurane						
WEEL (USA)	WEEL (USA) Long-term value: 1000 ppm					
101-68-8 4,4'-	101-68-8 4,4'-methylenediphenyl diisocyanate					
PEL (USA)	Ceiling limit: 0,2 mg/m³, 0,02 ppm					
REL (USA)	Long-term value: 0,05 mg/m³, 0,005 ppm Ceiling limit: 0,2* mg/m³, 0,02* ppm *10-min					
TLV (USA)	Long-term value: 0,051 mg/m³, 0,005 ppm					
EL (Canada)	Short-term value: C 0,01 ppm Long-term value: 0,005 ppm Skin; S					
EV (Canada)	Long-term value: 0,005 ppm					
156-60-5 tran	156-60-5 trans-dichloroethylene					
PEL (USA)	Long-term value: 790 mg/m³, 200 ppm					
REL (USA)	Long-term value: 790 mg/m³, 200 ppm					
TLV (USA)	Long-term value: 793 mg/m³, 200 ppm					
EL (Canada)	Long-term value: 200 ppm					
EV (Canada)	Short-term value: 990 mg/m³, 250 ppm Long-term value: 790 mg/m³, 200 ppm					

- · **DNELs** No further relevant information available.
- PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Clean skin thoroughly immediately after handling the product.

(Contd. on page 8)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 7)

· Respiratory protection:



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information. No further relevant information available.

9 Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosolized liquid with compressed gas in cylinders

Colour: Amber coloured

· Odour: Light

Petroleum-like

Odour threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range: Not Determined.

(Contd. on page 9)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 8)

Boiling point/Boiling range: -15 °F / -26 °C

· Flash point: Not applicable, as aerosol.

Flammability (solid, gaseous): Not applicable.
 Auto/Self-ignition temperature: Not determined.
 Decomposition temperature: Not determined.

· **Self-igniting:** Product is not self-igniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapour pressure:
Not determined.

1,02 g/cm³
Relative density
Not determined.
Vapour density
Not determined.
Vapour density
Not determined.
Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC (US EPA Method 24) 0 g/l

• **9.2 Other information** No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Develops readily flammable gases/fumes.

Reacts with oxidizing agents.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Contact with acids releases toxic gases.

Danger of receptacles bursting because of high vapour pressure when heated.

· 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

(Contd. on page 10)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 9)

Store away from oxidizing agents.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Hydrogen cyanide (prussic acid)

Phosphorus oxides (e.g. P2O5)

Chlorine

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

7104101	Additionally.					
· LD/LC5	· LD/LC50 values relevant for classification:					
101-68-	101-68-8 4,4'-methylenediphenyl diisocyanate					
Oral	LD50	2200 mg/kg (mouse)				
13674-8	13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate					
Oral	LD50	>2000 mg/kg (rat)				
Dermal	LD50	>2000 mg/kg (rabbit)				

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Subacute to chronic toxicity:

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Danger through skin adsorption.

Toxic and/or corrosive effects may be delayed up to 24 hours.

Suspected of causing cancer.

In addition to local irritant manifestations, there is a narcotic effect when inhaling high concentrations, with the danger of central respiratory arrest.

Asphyxiant gas.

- · Acute effects (acute toxicity, irritation and corrosivity): Vapours have narcotic effect.
- · Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

(Contd. on page 11)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 10)

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Carc. 2

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

The product contains materials that are harmful to the environment.

13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate

LC50 1,1 mg/l (Oncorhynchus mykiss) 96 h

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Avoid transfer into the environment.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · 14.1 UN-Number
- · DOT, ADR, IMDG, IATA

UN3500

(Contd. on page 12)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 11)

· 14.2 UN proper shipping name

• **DOT** Chemical under pressure, n.o.s. (Norflurane)

• ADR 3500 CHEMICAL UNDER PRESSURE, N.O.S.

(Norflurane)

• IMDG, IATA CHEMICAL UNDER PRESSURE, N.O.S. (Norflurane)

· 14.3 Transport hazard class(es)

· DOT



• Class 2.2 • Label 2.2

· ADR



· Class 2 8A Gases.

· Label 2.2

· IMDG, IATA



· Class· Label2.2

· 14.4 Packing group

· DOT, ADR, IMDG, IATA Not Regulated

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

Danger code (Kemler): 20EMS Number: F-C,S-V

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN3500, CHEMICAL UNDER PRESSURE, N.O.S.

(Norflurane), 2.2

(Contd. on page 13)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 12)

ARA	e substance or mixture
ection 355 (extremely hazardous substances):	
one of the ingredients is listed.	
ection 313 (Specific toxic chemical listings):	
016-87-9 diphenylmethanediisocyanate,isomeres and homologues	
01-68-8 4,4'-methylenediphenyl diisocyanate	
SCA (Toxic Substances Control Act):	
l ingredients are listed.	
oposition 65 (California):	
nemicals known to cause cancer:	
3674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate	
hemicals known to cause reproductive toxicity for females:	
one of the ingredients is listed.	
hemicals known to cause reproductive toxicity for males:	
one of the ingredients is listed.	
hemicals known to cause developmental toxicity:	
one of the ingredients is listed.	
arcinogenic Categories	
PA (Environmental Protection Agency)	
016-87-9 diphenylmethanediisocyanate,isomeres and homologues	CBD
01-68-8 4,4'-methylenediphenyl diisocyanate	D, CBI
56-60-5 trans-dichloroethylene	II
RC (International Agency for Research on Cancer)	
016-87-9 diphenylmethanediisocyanate,isomeres and homologues	;
01-68-8 4,4'-methylenediphenyl diisocyanate	;
LV (Threshold Limit Value established by ACGIH)	
one of the ingredients is listed.	
OSH-Ca (National Institute for Occupational Safety and Health)	
one of the ingredients is listed.	
anada	
anadian Domestic Substances List (DSL)	
l ingredients are listed.	
anadian Ingredient Disclosure list (limit 0.1%)	

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 13)

· Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225	Hiahly	flammable	liauid	and v	apour.

- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R40 Limited evidence of a carcinogenic effect.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic
 - environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 15)

Printing date 02.02.2017 Revision: 02.02.2017

Trade name: Touch N Seal Quick Cure Polyurethane Foam Sealant HY (High Yield)

(Contd. of page 14)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Press. Gas: Gases under pressure: Compressed gas Press. Gas: Gases under pressure: Dissolved gas Flam. Liq. 2: Flammable liquids, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· Sources

SDS Prepared by: ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com