

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

1 Identification

· Product identifier

· Trade name: Touch 'n Seal RF 60 CCMC Part A

Other product identifiers: EHS 2921 A

· Recommended use and restriction on use

· Recommended use: Polyurethane-sealant

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Convenience Products

866 Horan Drive Pacific, MO 63026 Phone: 636-349-5855

Phone: 636-349-5855 Toll-Free: 1-800-325-6180

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Press. Gas H280 Contains gas under pressure; may explode if heated.

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:







GHS04 GHS07 GHS08

· Signal word: Danger

Hazard statements:

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Cont'd. on page 2)

Page: 1/12



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 1)

Page: 2/12

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements:

P233 Keep container tightly closed.
P260 Do not breathe mist/vapors/spray.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection.
P284 In case of inadequate ventilation wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

Compone		
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	_ 25-50%
101-68-8	4,4'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
811-97-2	Norflurane Press. Gas, H280 Simple Asphyxiant	10-25%
	halogenated hydrocarbon Flam. Liq. 2, H225 Acute Tox. 4, H332	<10%

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

(Cont'd. on page 3)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 2)

Page: 3/12

For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure to call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Do not pull solidified product away from the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

Do not remove contact lenses if worn.

· After swallowing:

Unlikely route of exposure.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Asthma attacks

Headache

Allergic reactions

Coughing

Breathing difficulty

Dizziness

· Danger:

Danger of impaired breathing.

Danger of pulmonary edema.

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Condition may deteriorate with alcohol consumption.

· Indication of any immediate medical attention and special treatment needed:

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

Monitor circulation, possible shock treatment.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

· For safety reasons unsuitable extinguishing agents: None.

(Cont'd. on page 4)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 3)

Page: 4/12

· Special hazards arising from the substance or mixture

Danger of receptacles bursting because of high vapor pressure if heated.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

Carbon monoxide (CO)

In certain fire conditions, traces of other toxic gases cannot be excluded.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Remove persons from danger area.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Protect from heat.

Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Clean the affected area carefully; suitable cleaners are:

Warm water and cleansing agent

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Take note of emission threshold.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

(Cont'd. on page 5)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 4)

Page: 5/12

- · Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Store away from oxidizing agents.

Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:				
101-68-8 4,4'-methylenediphenyl diisocyanate				
PEL (USA)	Ceiling limit value: 0.2 mg/m³, 0.02 ppm			
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min			
TLV (USA)	Long-term value: 0.051 mg/m³, 0.005 ppm			
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S			
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm			
LMPE (Mexico)	Long-term value: 0.005 ppm			
811-97-2 Norflu	irane			
WEEL (USA)	Long-term value: 1000 ppm			
halogenated hy	ydrocarbon			
PEL (USA)	Long-term value: 790 mg/m³, 200 ppm			
REL (USA)	Long-term value: 790 mg/m³, 200 ppm			
TLV (USA)	Long-term value: 793 mg/m³, 200 ppm			
EL (Canada)	Long-term value: 200 ppm			
EV (Canada)	Short-term value: 990 mg/m³, 250 ppm Long-term value: 790 mg/m³, 200 ppm			
LMPE (Mexico)	Long-term value: 200 ppm			

- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Cont'd. on page 6)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 5)

Page: 6/12

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Engineering controls: No relevant information available.
- · Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

PVC gloves

Fluorocarbon rubber (Viton)

- · Not suitable are gloves made of the following materials: Natural rubber, NR
- · Eye protection:



Safety glasses

- · Body protection: Impervious protective clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties

Form: Color: Odor: Odor threshold:	Aerosolized liquid with compressed gas in cylind Cream colored Characteristic	lers
Odor:		
0.011	Characteristic	
Odor threshold:	or laractoricae	
Oddi diiodiiolai	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not applicable, as aerosol.	
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	400 °C (752 °F)	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 6)

Page: 7/12

Explosion limitsLower: Not determined.Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 5716 hPa (4287 mm Hg)

· Density:

Relative density: 1.03

Vapor density:Not determined.Evaporation rate:Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined. **Kinematic:** Not determined.

VOC content: 32.8 g/l

• Other information No relevant information available.

10 Stability and reactivity

- · **Reactivity:** No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Reacts with alcohols, amines, aqueous acids and alkalis.

Contact with acids releases toxic gases.

Danger of receptacles bursting because of high vapor pressure if heated.

Reacts with oxidizing agents. Exothermic polymerization.

- · Conditions to avoid Store away from oxidizing agents.
- · Incompatible materials Contact with acids liberates toxic gas.
- Hazardous decomposition products

Carbon monoxide and carbon dioxide

Ammonia

Isocyanate

Nitrogen oxides

(Cont'd. on page 8)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 7)

Page: 8/12

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Sensitization: May cause sensitisation by inhalation and skin contact.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Inhalation.

Eve contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Harmful if inhaled.

Irritating to eyes, respiratory system and skin.

- · Repeated dose toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · **STOT-single exposure**: May cause respiratory irritation.
- STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- Aquatic toxicity The product contains materials that are harmful to the environment.
- · Persistence and degradability The product is partially biodegradable. Significant residuals remain.
- · Bioaccumulative potential: Does not accumulate in organisms
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

This statement was deduced from products with a similar structure or composition.

(Cont'd. on page 9)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 8)

Page: 9/12

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- Waste treatment methods
- · Recommendation:

Contact waste processors for recycling information.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation:

Packagings that cannot be cleansed are to be disposed of in the same manner as the product. Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3500
UN proper shipping name	
· DOT, IATA	Chemical under pressure, n.o.s. (Fluorinate hydrocarbon, Nitrogen)
· ADR, IMDG	CHEMICAL UNDER PRESSURE, N.O.S (FLUORINATED HYDROCARBON, NITROGEN)
· Transport hazard class(es)	
· DOT	
· Class	2.2
	(Cont'd. on page '



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 9) · Label 2.2 · ADR · Class 2 8A Gases · Label 2.2 · IMDG, IATA · Class 2 Gases · Label 2.2 · Packing group This UN-number is not assigned a packing group. • Environmental hazards · Marine pollutant: No Special precautions for user Warning: Gases Danger code (Kemler): 20 · EMS Number: F-C,S-V Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

(Cont'd. on page 11)

Page: 10/12



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 10)

Page: 11/12

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories

	· EPA (Environmental Protection Agency):			
Ī	9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	CBD	
101-68-8 4,4'-methylenedipher		4,4'-methylenediphenyl diisocyanate	D, CBD	
		halogenated hydrocarbon	II	

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision April 10, 2017 / -

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Press. Gas: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

(Cont'd. on page 12)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 10, 2017 Revision: April 10, 2017

Trade name: Touch 'n Seal RF 60 CCMC Part A

(Cont'd. of page 11)

Page: 12/12

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by: ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com